16CH NVR

NVR8-16400A(1U)



















DDNS













MC	ODEL		NVR8-16400A(1U)
		Input	16CH Over Network
Video		Output	HDMI (4K, 1080P), VGA (1080P, 1280x1024, 1024x768)
		Decoding Format	H.265 (HEVC) / H.264
		Decoding Capabilities	1Ch - 8MP ; 4Ch - 2MP ; 9/16Ch - D1
Analytics		Analytics Channels	16Ch (Requires supporting IPC)
		Supported Analytics	Smart Search, Camera Tampering, Line Crossing, Sterile Area, Object Monitoring
		Face Recognition	Not Supported
Audio		Input	1CH + Depends on Camera Inputs
		Output	1CH + Depends on Camera Outputs
		Two Way Audio	Yes
		Incoming	112Mbps
Ba	ndwidth	Outgoing	112Mbps
	Record/ Main Stream	Real-Time Recording	16CH 8MP Real-Time
Record / Remote App.		8MP	480FPS (NTSC)/400FPS (PAL)
		5MP and lower	480FPS (NTSC)/400FPS (PAL)
		Master Streams over Network	Up to 16CH@Recording Resolution
		Resolution	Depends on IPC
	Stream	Sub-Streams over Network	Up to Outgoing Bandwidth Capacity
	General	User Access	10 Users Online with Professional Autorithy Management
		Recording Modes	Schedule, Manual, Motion, Sensor, Analytics
			Provision Cam2 for iOS/Android, IE for Windows 7/8/10, Safari for Mac OS, CMS for Windows/MAC
		Applications Playback (Local / Pomoto)	16CH / 16CH
Playback		Playback (Local / Remote) Search Mode	Smart Search, Time-Slice, Time, Event, File Management
Backup		USB	2 USB 2.0 Ports
			AVI/DAT
Alarm		Backup Format	4CH + Depends on Camera
		Input	1CH + Depends on Camera
		Output	2 SATA (8TB Each)
		HDD	No
		E-SATA	
		RAID	Not Supported
PTZ		Connection	Via Network
		Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
		RS-485	No No
Network PoE		Ethernet	1000 Mbps (RJ-45)
		Protocols	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP, FTP, HTTPS
		ONVIF	Yes (For IP Channels)
		Ports	No
		Interface	No
		Standard	No
		Total Power	No
		Max. Power Output (Per Ch.)	No
		Power Supply	DC12V/4A
Others		Power Consumption (No HDD)	5W
		Dimention	W375xD275xH50mm
		Operation Temperature	0°C ~50°C