Product data sheet



NXG-1830-EUR

xGen & xGenConnect keypad, white

General

The new state-of-the-art LCD keypads for the xGen and xGenConnect series of security systems are bringing a new and modern looking user interface that fits virtually any décor. Its attractive design will please home owners while its robust design will make it stand out in a commercial environment or any other type of business. The keypad door can be turned up to hide the buttons when not using the system or it can easily be taken off to allow faster operation.

System Information

A large graphical display makes system messages easily readable. The user can chose from a various number of colour schemes for the background light of both the display and the buttons and this to make the keypad seamlessly fitting any type of décor. In the blink of an eye, a multi-colour ring shape status indicator will alert the user in case of an incident or fault, or will simply provide the system status.

Operation

Large buttons and a selection of background ambient light ensure error free operation, even in a darkened environment. Dedicated buttons will also be used to navigate the user easily through the programming and operational features.

Four pre-programmed function buttons allow the user to perform the most common functions. Arm the system perimeter with the possibility to differentiate between Arm Stay, Arm Stay Instant, Arm Stay Night. Fully arm the system when exiting the premises. An Off or Disarm button to disarm the system or clear fault messages and an Info button to retrieve system status information.

Four special buttons are available with combined functionality for simplified operation. A single touch of the button will initiate features like manual bypass, enable the "chime" mode or trigger a scene. When pressing the button for two seconds the button can signal a fire or medical emergency or can activate a hold-up alarm.

Installation

The keypad backplate has the mounting points in the same position as the legacy NetworX keypads so no additional drilling is required when replacing legacy keypads when migrating to the xGenConnect security system. The backplate also allows easy cable entry and incorporates cable conduits from four directions.



Details

- Modern design with removable door
- Multi-colour graphical display
- · Various button and display colour schemes
- Multi-colour status indicator
- White and anthracite variant
- 3 arming modes: Arm Away, Arm Stay, Arm Stay Night
- 4 programmable function buttons (A/B/C/D)
- · Single and multi-partition operation
- Multi-language support
- Conduits for easy cable entry
- Custom logo on display
- Navigation menu for user and installer
- Firmware upgradeable via USBUP and DLX900
- EN 50131-3 Security Grade 2, INCERT T031

NXG-1830-EUR

xGen & xGenConnect keypad, white

Technical specifications

General	
Panel compatibility	xGen and xGenConnect
Communication	
Communication type	Wired
Wiring	RS-485, 4-wire bus
System	
Function keys	4
Programmable keys	4
Ambient colour	white, pink, violet, blue, cyan, green, lime, yellow, orange, red
Electrical	
Operating voltage	9 to 15VDC (provided by panel)
Minimal current consumption (all lights off)	35 mA at 13.7 VDC
Nominal current consumption	90 mA at 13.7 VDC
Maximum current consumption	160 mA at 13.7 VDC
Physical	
Physical dimensions	133 x 130 x 25 mm
Net weight	0.3 kg
Colour	White
Connector type	Removable connector
Environmental	
Operating temperature	-10 to +50°C
Relative humidity	95% non-condensing
Environment	Indoor
Standards & regula	ation
Standards	EN50131 Grade 2 INCERT T031 Grade 2

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

