


## POWER: 30VA

### Features

- Epoxy resin cast
- Two chambers bobbin
- Insulation primary-secondary: 4KV-1p
- Increased humidity resistance

### Manufacturing standard: EN 61558

- Safety insulation transformer
- Max. ambient temperature:  $t_a$  50°C
- Insulation class: B 130°C
- Double insulated
- Degree of protection: IP00
- Conditionally short-circuit safe



### Application

- For power supply of safeguarding centres
- For power supply of other electrical devices

### Application features

- Mechanical fixing possibility for direct
- Built-in primary fuse
- Connection with terminal block connectors
- Cross section of cables max. 1.5 mm<sup>2</sup>

Model number	Primary voltage	Secondary voltage	Secondary current
ME.TRE-30.60112/BSS 30VA	230V-50Hz	12 V	2,50 A
ME.TRE-30.60116/BSS 30VA	230V-50Hz	16.5 V	1,81 A
ME.TRE-30.60118/BSS 30VA	230V-50Hz	18 V	1,66 A
ME.TRE-30.60124/BSS 30VA	230V-50Hz	24 V	1,25 A
ME.TRE-30.60140/BSS 30VA	230V-50Hz	40 V	0,75 A
Prescribed primary circuit fuse: 250 mA T			
Tolerance of secondary voltage: 5%			