



EN54-3 Type B
CERTIFIED
1328-CPR-0300



VALKYRIE CS IP65

Conventional Wall Mount Sounder/ Beacon Outdoor Use-IP65

The VALKYRIE CS IP65 is a wall mounted Conventional Sounder/ Beacon with low power consumption. It is specifically designed to be used outdoors. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS		
SUPPLY VOLTAGE		20 V to 30 V DC
CURRENT - SOUNDER/ BEACON ACTIVE		10 mA - 280 mW @ 30 V DC
MAXIMUM SOUNDER OUTPUT		97 dB (@ 1 meter - 30 V DC)
MAX. CABLE SIZE		2.5 mm ²
OPERATING TEMPERATURE		-20°C to 70°C
MAX. HUMIDITY		95% RH Non-Condensing
COLOUR / CASE MATERIAL		Red / ABS and PC
PROTECTION CATEGORY		IP65 - Type B - Outdoor use
DIMENSIONS		112 (D) x 110 (H) mm inc. base
WEIGHT		315 g / 350 g - including packaging
ORDER CODE		
VALKYRIE CS IP65	1328-CPR-0300	CONVENTIONAL WALL SOUNDER - IP65 RATED
VALKYRIE CSB IP65	1328-CPR-0300	CONVENTIONAL WALL SOUNDER/ BEACON - IP65 RATED